

## CLAIMS

Sub  
a2  
5 1. An electronic input device comprising:  
a flexible input means for receiving user input; and  
a housing defining a space for accommodating said input means; wherein  
said input device has a first state and a second state; and  
the input means adopts a compacted spatial configuration in the first state  
and adopts an extended spatial configuration in the second state.

10 2. An electronic input device according to claim 1, wherein the input means has  
an input surface having touch sensitive areas.

15 3. An electronic input device according to claim 1, wherein the extended spatial  
configuration is planar.

4. An electronic input device according to claim 1, wherein the compacted  
spatial configuration is non-planar.

20 5. An electronic input device according to claim 1, wherein in the compacted  
spatial configuration the input means is wound into a roll.

6. An electronic input device according to claim 1 further comprising means for  
moving said input means between said first and second configurations.

25 7. An electronic input device according to claim 1, wherein said input means is a  
keyboard.

8. An electronic input device according to claim 1, wherein said input means is  
also a display.

30 9. An electronic input device according to claim 1 further comprising:  
a flexible output means for outputting information; and

a housing defining a space for accommodating said output means;  
wherein

said input device has a first state and a second state; and

the output means adopts a compacted spatial configuration in the first  
5 state and adopts an extended spatial configuration in the second state.

10. An electronic input device according to claim 9, wherein said output means is  
a display.
- 10 11. An electronic input device according to claim 9, wherein said output means is  
arranged parallel with said input means so that the input device has two  
states corresponding to the first and second states of both input means and  
output means.
- 15 12. An electronic input device according to claim 9 further comprising a hinge for  
foldingly connecting the housing defining the space for accommodating said  
output means to the housing defining a space for accommodating input  
means.
- 20 13. An electronic input device according to claim 1, wherein the electronic input  
device is a telecommunications device.
14. An electronic input device according to claim 13 further comprising:  
two elements, which are foldable about a hinge between an open  
25 configuration and a closed configuration;  
a speaker located in one element, and  
a microphone in another element so that the electronic input device can  
be unfolded to separate the microphone and the speaker.
- 30 15. An electronic input device according to claim 14 further comprising:  
a stop to resist opening the two elements of the input device over a certain  
maximum opening angle; and

00502T 95002650

means for changing the maximum opening angle when the configuration of the device is changed between the compacted spatial configuration and the extended spatial configuration.

5 16. A method for manufacturing of an electronic input device comprising the steps of:

forming to the electronic input device a housing to define a space for accommodating a flexible input means; and

10 inserting a flexible input means in a compacted spatial configuration at least partially into said space.

17. A method for manufacturing of an electronic input device comprising the steps of:

15 forming to the electronic input device a housing to define a space for accommodating a flexible input means;

shaping the flexible input means into a compacted spatial configuration; and

inserting the flexible input means at least partially into said space.

20 18. A method of an electronic input device presenting a user interface, comprising the steps of:

storing a flexible input means in a compacted spatial configuration within a housing of the electronic input device;

25 extending the flexible input means out of the housing into an extended spatial configuration for receiving user input; and

retrieving the flexible input means again into the compacted spatial configuration within the housing.

005021 9906260